



F3 RE 10/17/22 AM . RETRACTABLE TAIL-LIFT ALUMINIUM GUIDES - 5 CYLINDERS

LOAD CAPACITY

- 1000 KG
- 1700 KG
- 2200 KG



TECHNICAL SPECIFICATIONS

Cylinders:	2 lift cylinders + 2 tilt cylinders + 1 automatic tilt cylinder
Sliding system:	Aluminium sliding , hydraulic motor + pinion and rack
Tilt cylinders:	Single acting
Automatic tilt at ground level:	Yes, Hydraulic
Platform material:	Aluminium
Standard platform depths Alu:	1 fold 1493 - 1638 - 1783 mm (max 2033) 2 folds 1333 - 1633 - 1833 mm
Standard platform widths Alu:	2100 - 2250 - 2400 mm (Max 2500)
Lift arm lengths:	C - H - HS - HSS
Lift arm widths (W):	780 -1230 - 1520 mm
Standard control:	Unit Exterior control box with joystick, turn button

APPLICATIONS

F3RE 10/17/22 AM with Aluminium Sldyers, so attractive pricing and ideal to equip rental vehicles.

The 5 cylinders F3RE 10/17/22 AM is a strong and compact lift, with very high performances.

Smooth hydraulic automatic tilt, high stiffness ideal to equip vehicles for customers that like high performances.

The 5 cylinders a F3RE 10/17/22 AM is available with a wide variety of versions, to suit commercial trucks above 7.5T GVW, rigids, trailers and semi-trailers.

	Mod.	Load capacity (center of gravity at 600 mm)	E max	Platform Depth* (example)	SIDE FITTING FOR RIGID VEHICLE				QUICK FITTING FOR SEMI-TRAILER			
					B min	B' min	T	Weight** Kg	B min	B' min	T	Weight* Kg
1 FOLD PLATFORM	F3 RE 10 C AM	1000 kg	1115	1560 (600 + 960)	1473	1579	342	430	-	-	-	-
	F3 RE 17 C AM	1700 kg	1130	1433 (550 + 883)	1454	1524	318	470	-	-	-	-
	F3 RE 22 C AM	2200 kg	1130	1433 (550 + 883)	1454	1524	318	490	-	-	-	-
	F3 RE 10 H AM	1000 kg	1275	1560 (600 + 1005)	1575	1680	342	455	-	-	-	-
	F3 RE 17 H AM	1700 kg	1290	1633 (750 + 883)	1756	1826	318	505	1750	1825	487	502
	F3 RE 22 H AM	2200 kg	1290	1633 (750 + 883)	1756	1826	342	525	1750	1825	487	522
	F3 RE 10 HS AM	1000 kg	1510	1755 (750 + 1005)	1878	1983	342	480	1903	1978	487	517
	F3 RE 17 HS AM	1700 kg	1530	1633 (750 + 883)	1909	1979	318	520	1903	1978	487	537
	F3 RE 22 HS AM	2200 kg	1530	1633 (750 + 883)	1909	1979	318	540	1903	1978	487	537
2 FOLDS PLATFORM	F3 RE 17 C AM	1700 kg	1130	1083 (600 + 483)	1123	1093	375	450	-	-	-	-
	F3 RE 22 C AM	2200 kg	1130	1083 (600 + 483)	1123	1093	375	470	-	-	-	-
	F3 RE 10 H AM	1000 kg	1275	1305 (700 + 605)	1082	1197	342	395	-	-	-	-
	F3 RE 17 H AM	1700 kg	1290	1283 (700 + 583)	1226	1196	375	485	1220	1221	544	482
	F3 RE 22 H AM	2200 kg	1290	1283 (700 + 583)	1226	1196	375	505	1220	1221	544	502
	F3 RE 10 HS AM	1000 kg	1510	1600 (850 + 750)	1245	1350	342	460	-	-	-	-
	F3 RE 17 HS AM	1700 kg	1530	1583 (850 + 733)	1379	1346	375	520	1373	1374	544	517
	F3 RE 22 HS AM	2200 kg	1530	1583 (850 + 733)	1379	1346	375	540	1373	1374	544	537

*Platforms depth from 1333 mm to 1983 mm. **Approximate weight for tail-lift with platform width 2450 mm. Centre of gravity of the vehicle depending on the type of arm and the size of the installations on the vehicle (see assembly instructions). The above mentioned weights are approximate and may vary according to production. Anteo reserves the right to change weights and technical specifications without prior notice. No indemnity for damages can be claimed from Anteo for changes in technical specifications and/or in weight.



F3 RE 10/17/22 AM . RETRACTABLE TAIL-LIFT ALUMINIUM GUIDES - 5 CYLINDERS

LOAD CAPACITY

- 1000 KG
- 1700 KG
- 2200 KG



Option:
fully pre-
assembled
platform,
controls and
guides on
request.




Hydraulic motor and brake (patented)




Power pack




Control box



Side fitting for rigid vehicle
1 fold platform



Side fitting for rigid vehicle
2 folds platform



Quick fitting for semi-trailer
1 fold platform